Styleline FX



STYLELINE® FX sets a new standard in protection against condensation by providing advanced thermal design fully compliant with DOE 2017 regulations.

Available for cooler and freezer applications, STYLELINE® FX door and frame system is ideal for those high-end applications without sacrificing performance and elegance!

- Elegant edge-to-edge glass appearance
- Proven hardware simplicity and reliability
- Pre-wired energy controller
- STYLELINE LED Plus included





All Glass Appearance Door!





APPLICATION: Cooler, High Humidity and Freezer

Same level and performance expectation with PROTECTION: greater energy savings and efficiency

LIGHTING: Styleline LED Plus

2-years workmanship and materials, WARRANTY: 5-years LED, 10-years non-heated glass pack

- Edge-to-edge glass door with elegant low-profile trim
- Fully compliant with DOE 2017 regulations
- 2 pane glass pack (cooler), Argon fill
- 3 pane glass pack (high humidity, freezer), Argon fill, Low-E
- Energy controller for high humidity and freezer applications
- Advanced thermal glass pack design delivers enhanced condensation protection with very low energy use
- STYLELINE® reliable door hinge, hold open cam, one-time adjustment torque rod and self-closing hinge system
- Stainless steel trim & new and improved magnetic door aasket desian

What's Included:

- STYLELINE® LED Plus lighting system
- Five heavy-duty 27" NSF approved black shelves and post with price tag molding and black brackets. White shelves with galvanized post and galvanized brackets are also available
- Standard STYLELINE® Warranty



Finishes







Post Colors

Door Size W x H	24" x 63"	26" x 63"	30" x 63"	26" x 72"	24" X 72"	26" x 80"	30" x 72"	30" x 80"
NCO Height	64 3/4"	64 3/4"	64 3/4"	73 3/4"	73 3/4"	81 5/8"	73 3/4"	81 5/8"
Doors	NCO Width							
1	2' 11/16"	2' 313/16"	2' 73/4"	2' 3 13/16"	2' 11/16"	2' 313/16"	2' 73/4"	2' 73/4"
2	4' 13/16"	4' 65/16"	5' 23/16"	4' 65/16"	4' 13/16"	4' 65/16"	5' 23/16"	5′ 23/16″
3	6′ 9/16″	6' 813/16"	7' 85/8"	6' 813/16"	6′ 9/16″	6' 813/16"	7' 85/8"	7' 85/8"
4	8′ 5/16″	8′ 115/16″	10′ 31/16″	8′ 115/16″	8′ 5/16″	8' 115/16"	10′ 31/16″	10′ 31/16″
5	10′ 1/16″	11' 113/16"	12′ 91/2″	11' 113/16"	10′ 1/16″	11′ 113/16″	12' 91/2"	12′ 91/2″
6	12′ 213/16″	13' 75/16"	15' 615/16"	13' 75/16"	12' 213/16"	13' 75/16"	15' 615/16"	15' 615/16"
7	14' 29/16"	15' 913/16"	18' 13/8"	15' 913/16"	14' 29/16"	15' 913/16"	18' 13/8"	18' 13/8"
8	16' 25/16"	18' 5/16"	20' 713/16"	18' 5/16"	16′ 25/16″	18' 5/16"	20' 713/16"	20' 713/16"
9	18′ 21/16″	20′ 213/16″	23′ 21/4″	20′ 213/16″	18′ 21/16″	20′ 213/16″	23′ 21/4″	23′ 21/4″
10	20′ 113/16″	22′ 55/16″	25' 811/16"	22′ 55/16″	20′ 113/16″	22′ 55/16″	25' 811/16"	25′ 811/16″

Complete chart available at styleline.com

Shelving Size	Description / Information				
24" x 27", 26" x 27", 30" x 27"	*Five Standard (black/white) Heavy-Duty epoxy and NSF approved				
30" x 36"	*Five Standard Slide Trac™ Gravity-flow (black/white) Heavy-Duty epoxy and NSF approved				

Seven shelves with 80" Size Doors

Options Available:

- Anti-fog film
- White/Black shelf post
- On/Off light switch
- Slide-Trac® shelving system
- Super Slide-Trac® gravity-flow shelving system

